



Description

Venture Lighting's Select-Pro Back-lit LED Panels are low profile, lightweight, and designed for long life and low maintenance. These luminaires are designed to quickly and easily upgrade existing fluorescent fixtures and be more versatile than other LED panels. Each panel is capable of changing to 3 different CCT settings (3500K, 4000K, 5000K) and 3 different wattage settings (3 light levels) with a simple slide switch. The flexible selection capability allows for a cost-effective method to reduce stocking inventory by 88% (1 SKU instead of 9).

Construction

The housing features a metal back plate and metal driver with 5 knockout integrated junction box. The seamless frame is constructed of aluminum that is painted white.

Optics

Each LED has an integrated wide distribution optic designed to provide even illumination without producing visible hot spots.

Electrical

The driver comes prewired with one black input lead (hot), one white input lead (neutral) and one green ground lead. 0-10V DC continuous dimming capability is standard.

Mounting

The panel can be mounted in a recessed ceiling, surface mounted (optional), or suspended (optional). The panel is designed for replacing fluorescent fixtures in T-bar drop ceilings. The panel back plate includes integral T-bar clips for installation onto standard 15/16" T-grid ceilings or narrow 9/16" T-grid ceilings.

Warranty

For warranty information refer to:
www.venturelighting.com/resources/warranties

Order Code/DLC Model No: PB224-45-UNV-C&W

Product Performance

Wattage	3500K CCT Lumen Output	4000K CCT Lumen Output	5000K CCT Lumen Output
45W	5150	5350	5250
35W	4000	4150	4050
30W	3400	3550	3500
Color Rendering Index (CRI)			≥ 80
Life Hours			≥ 50,000
Operating Temperature Range		-13°F to 104°F (-25°C to 40°C)	

Physical Characteristics

Fixture Color	White
Panel Size	2x4
Width	23.76" (604.3mm)
Length	47.76" (1214.3mm)
Height	1.66" (42.2mm)
Weight	9.45 lbs (4.28 kg)

Electrical Characteristics

Input	120-277V, 60Hz, 0.40A Max
Power Factor	≥ 90%
THD	≤ 20%
Dimming	0-10V DC continuous

Regulatory Qualifications

cETLus Listed; DLC® Qualified

Type IC, inherently protected luminaire

Dry and damp location rated (IP20)

Accessories

KT48114 2X4 Surface Mount Kit, White

KT18916 2X4 Drywall Mount Kit, White

KT23279 Battery Backup Kit, 2X2, 2X4

AC25420 3/8" 3-Wire 14/3 600V Max 6ft Flex Whip

AC25418 - 3/8" 4-Wire 14/4 6ft Flex Whip

AC25425 - 1/2" 5-Wire 14/3, 18/2 6ft Flex Whip

AC25426 - 1/2" 6-Wire 14/4, 18/2 6ft Flex Whip


Add suffix "-WP" to fixture model # for a factory-installed 6ft whip

Add Suffix "-EM" to fixture model # for a factory-installed battery

Revision: 1, 02-Nov 2023

Select-Pro CCT/Wattage Selectable 2x4 LED Panel

Dimensions



(800) 451-2606

6675 Parkland Blvd., Suite 100

Solon, Ohio 44139 USA

Email: Venture_Lighting@VentureLighting.com

VentureLighting.com

