




**HIGH
PRESSURE
SODIUM**



Universal
Any Position

E17



Dia. = 2.1" (54mm)
MOL = 5.7" (145mm)
LCL = 3.7" (93mm)
Base = Medium (E26)

LU150/55/MED/ECO GENERAL Characteristics

Lamp Type	HPS Single Ended
ANSI Code	S55
Bulb Shape	E17
Base Type	Medium (E26)
Bulb Finish	Clear
Rated Life	24000 hours
Operating Position	Universal

PHOTOMETRIC

Initial Lumens	15800
Lumens Per Watt	105
Lamp Lumen Depreciation (LLD)	0.90 (90%) @ 12000 hours
Correlated Color Temperature	2100K
Chromaticity Coordinates (CIE-x,y)	.522 .423
Color Rendering Index (CRI) R_a	22

PHYSICAL

Bulb Diameter	2.1" (54mm)
Max. Overall Length (MOL)	5.7" (145mm)
Light Center Length (LCL)	3.7" (93mm)
Effective Arc Length	N/A
Max. Base Temperature (°C)	190
Max. Bulb Temperature (°C)	400
Socket Pulse Rating (KV)	4
Luminaire Type	Enclosed Rated

ELECTRICAL

Lamp Watts	150
Lamp Oper. Voltage (Nom.)	55

SUSTAINABILITY

Mercury Amount (mg)	12.0
Picograms of Hg per Mean Lumen Hour	35

NOTES

- TCLP Compliant - Lamp passes the EPA Toxicity Characteristic Leaching Procedure test
- Product may contribute towards satisfying MR-Credit 4 under LEED.

(800) 451-2606

6675 Parkland Blvd., Suite 100

Solon, Ohio 44139 USA

E-mail: Venture_Lighting@VentureLighting.com

VentureLighting.com