





**HIGH  
PRESSURE  
SODIUM**



**Universal**  
Any Position

**E17**



Dia. = 2.1" (54mm)  
MOL = 5.7" (145mm)  
LCL = 3.7" (93mm)  
Base = Medium (E26)

## LU150/55/D/MED GENERAL Characteristics

Lamp Type	HPS Single Ended
ANSI Code	S55
Bulb Shape	E17
Base Type	Medium (E26)
Bulb Finish	Coated
Rated Life	24000 hours
Operating Position	Universal

## PHOTOMETRIC

Initial Lumens	14500
Lumens Per Watt	97
Lamp Lumen Depreciation (LLD)	0.90 (90%) @ 12000 hours
Correlated Color Temperature	2100K
Chromaticity Coordinates (CIE-x,y)	.522 .423
Color Rendering Index (CRI) $R_a$	22

## PHYSICAL

Bulb Diameter	2.1" (54mm)
Max. Overall Length (MOL)	5.7" (145mm)
Light Center Length (LCL)	3.7" (93mm)
Effective Arc Length	N/A
Max. Base Temperature (°C)	190
Max. Bulb Temperature (°C)	400
Socket Pulse Rating (KV)	4
Luminaire Type	Enclosed Rated

## ELECTRICAL

Lamp Watts	150
Lamp Oper. Voltage (Nom.)	55

## SUSTAINABILITY

Mercury Amount (mg)	12.0
Picograms of Hg per Mean Lumen Hour	38

## NOTES

- Product may contribute towards satisfying MR-Credit 4 under LEED.

**(800) 451-2606**

6675 Parkland Blvd., Suite 100

Solon, Ohio 44139 USA

E-mail: [Venture\\_Lighting@VentureLighting.com](mailto:Venture_Lighting@VentureLighting.com)

**VentureLighting.com**