

48W LED Panel (2x4), 3500K

Order Code: PN41312



Description

The Venture Lighting LED panel series of luminaires are low profile, lightweight, and designed for long life and low maintenance. These are designed to quickly and easily upgrade existing fluorescent fixtures. LED color consistency meets a 4-step MacAdam ellipse.

Construction

The high-performance LED source is mounted to ensure proper thermal management of the system. The design allows for a cooler running LED chip which leads to longer lifetime, better efficacy, and color consistency.

Optics

The fixtures are designed to have low glare yet utilize high performance materials to maximize efficacy and achieve precise photometric distributions.

Electrical

The power supply has a range of 200-347V, 50/60 Hz. 0-10V DC dimming capability is standard. The fixture is rated for damp and dry locations. Fixtures are IC-rated.

Mounting

The fixture is designed for replacing fluorescent fixtures.

Warranty

For warranty information refer to: www.venturelighting.com/resources/warranties

48W
5170
3500K
80
50,000
-13°F to 113°F (-25°C to 45°C)
White
47.7"
23.7″
1.9″
1.7
2x4

Electrical Characteristics

Amperage Draw (Input Volts/Amps)

347/0.16

Regulatory Qualifications

cULus Listed

IC-rated

Accessories

AC25420 - 3/8" 3-Wire 14/3 600V Max 6ft Flex Whip

KT18522 – 2x4 Surface mount kit, white KT18916 – 2x4 Drywall mount kit, white


Add suffix "-WP" for factory installed fixture with 6ft whip (AC25420)

Revision: 05, 06-Sept 2022





Venture 40W LED Panel (2x2), 4000K

Dimensions



Luminious Intensity Distribution Diagram





(800) 451-2606

6675 Parkland Blvd., Suite 100 Solon, Ohio 44139 USA Email: Venture_Lighting@VentureLighting.com

VentureLighting.com

